



TCH/5

🇮🇹 Chiave a Doppia Mappa

- Struttura monoblocco in lamiera d'acciaio dello spessore di 2 mm.
- Porta spessore 3 mm.
- Spessore totale del battente 55 mm.
- Serratura di sicurezza a 6 leve con chiave a doppia mappa.
- Estrazione della chiave impossibile a catenacci rientrati.
- 4 catenacci frontali in acciaio nichelato del Ø di 20 mm.
- Rastrelliera in legno ricoperta in tessuto e tappetino sulla base.
- Tesoretto interno portamunizioni con serratura a cilindro.
- Fori di ancoraggio sulla base e sullo schienale (2+2).
- Verniciatura con polvere epossidica.

TCH/5: • con tesoretto - 5 fucili

TCH/10: • con tesoretto - 10 fucili

🇬🇧 Double-Bitted Key

- One-piece steel construction with a body's thickness of 2 mm.
- Thickness of door 3 mm.
- Total door thickness (with lock-panel): 55 mm.
- Security lock with 6 levers and double-bitted key.
- Key-retaining lock in open position.
- 4 frontal nickel-plated steel bolts Ø 20 mm.
- Equipped with wood supports covered with textile and inside base with carpet.
- Internal security box with cylinder lock.
- Pre-drilled anchor holes on floor and wall mounting (2+2).
- Painting with epoxy powder.

TCH/5: • with sec. box - 5 rifles

TCH/10: • with sec. box - 10 rifles



Art Code	Misure esterne mm. External dim. mm.			Misure interne mm. Internal dim. mm.			Dim. porta mm. Door dim. mm.		Numero catenacci Number of bolts	Peso Weight	Litri Volume	
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Kg	Lt	
TCH/5	1450	340	280	1300*	335	245	1325	270	4	44	119	
TCH/10	1450	535	320	1300*	530	285	1325	460	4	74	218	

* Esclusa l'altezza della cassetta interna

* Excluding the high of security box