



SMKO/3

- Frontale e Porta 8 mm
- Corpo 3 mm
- Taglio Laser

- *Front and Door 8 mm*
- *Body 3 mm*
- *Laser Cut*



🇬🇧 Double-Bitted Key

- Security lock EN 1300 certified, with 8 asymmetrical and independent levers lock with double-bitted key.
- Key-retaining lock in open position.
- Nickel-plated rotating steel bolts Ø 22 mm.
- Lock mechanism protected by a manganese-steel plate.
- Special ledges of the door particularly resistant.
- Strong internal welding realised by a robot-controlled system.
- Front panel seam-welded to the casing by a robot-controlled system.
- Removable shelf (excluded the SMKO/1 and SMKO/2 models).
- Base and back fixing holes (2+2), anchor fixing bolts provided
- Oven dried thermo-hardening powder painting.

| Art Code | Misure esterne mm. | | | Misure interne mm. | | | Dim. porta mm. | | Numero catenacci | | | Peso | Litri |
|-------------|--------------------|--------|--------|--------------------|--------|--------|----------------|--------|------------------|------|------|------|-------|
| | Alt/H | Larg/W | Prof/D | Alt/H | Larg/W | Prof/D | Alt/H | Larg/W | Oriz/Horiz | Vert | Kg | Lt | |
| SMKO/1 | 220 | 280 | 150 | 210 | 270 | 90 | 130 | 180 | 2 | - | 10 | 6 | |
| SMKO/2 | 220 | 280 | 200 | 210 | 270 | 140 | 130 | 180 | 2 | - | 11 | 9 | |
| SMKO/3 | 220 | 350 | 300 | 210 | 340 | 240 | 130 | 250 | 2 | - | 17 | 19 | |
| SMKO/4 | 280 | 400 | 350 | 270 | 390 | 290 | 180 | 300 | 2 | 1+1 | 24,5 | 31 | |